Model: **CS-82A** 2 Port PS/2 KVM Switch Model: **CS-84A** 4 Port PS/2 KVM Switch







CS-84A Rear View

A compact and rugged solution for managing up to two to four PCs. Access the CS-82A/84A KVM Switch (Compatible with PS/2 and USB\*) through push buttons on the front panel or hotkey combinations from the keyboard. Featuring a durable exterior and compact form factor, the console connector ports are ergonomically located on the front panel for easy accessibility while the foot pads prevent desktop sliding.

\* USB operation requires purchase of optional equipment (see below).


### **Features**

- PS/2 compatible mouse supports Microsoft Intellimouse pro, Logitech FirstMouse support
- Connector placement specifically designed for neat and tidy cable attachment
- Supports 1920 x 1440 resolution, DDC2B
- Scan mode automatically switches between PCs

## **Specifications**

			I	
Function			CS-82A	CS-84A
Computer Connections			2	4
Computer Port Selection			Hotkey, Push button	
Connectors	Console	Keyboard	1 x Mini Din 6 Female (Purple)	
		Video	1 x HDB15 Female (Blue)	
		Mouse	1 x Mini Din 6 Female (Green)	
	Computer	Keyboard	2x Mini Din 6 Female (Purple)	4x Mini Din 6 Female (Purple)
		Video	2 x HDB15 Male (Blue)	4 x HDB15 Male (Blue)
		Mouse	2x Mini Din 6 Female (Green)	4x Mini Din 6 Female (Green)
	Power		1 x DC Jack (Spare)	
LEDs	On Line		2 (Orange)	4 (Orange)
	Selected		2 (Green)	4 (Green)
Emulation	Keyboard		PS/2	
	Mouse			
Video			1920 x 1440; DDC2B	
Scan Interval			3, 5, 10, 20 Seconds	5 Seconds
Power Consumption			DC9V, 1.080W	DC9V, 1.17W
Environment	Operating Temperature		0°~50°C	
	Storage Temperature		-20°~60°C	
	Humidity		0~80% RH, NC	
Physical Properties	Housing		Metal	
	Weight		0.42 kg	0.64 kg
	Dimensions (L x W x H)		14 x 8.5 x 5.5 cm	21 x 8.5 x 5.5 cm

## Diagram



Console

# Accessories



1.2m PS/2 KVM cables x 2 (CS-82A) 1.2m PS/2 KVM cables x 2 / 1.8m PS/2 KVM cables x 2 (CS-84A)

#### **Optional Equipment**

## Cables & Converters for USB interface support:

- **1. PC compatible:** a 1.8m (2L-5502UP), or 3m (2L-5503UP) and 6m (2L-5506UP) USB KVM cable, please refer to page P64-G
- 2. Windows/Mac compatible: UC-100 KMA (PS/2 to USB Adapter), please refer to page P35
- 3. Sun (USB): CV-131B, see page P34, SUN (Legacy): CV-130B, see page P33
- 4. A DC9V power adapter is available- requires separate purchase











