

Bike adhesive lubricant with PTFE, MoS2 RP0024

Revision date: 15.01.2024

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Bike adhesive lubricant with PTFE, MoS2 RP0024

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricants, greases, release products

1.3. Details of the supplier of the safety data sheet

Company name:	2direct GmbH	
Street:	Langenstück 5 / Industriegebiet Golsberg	
Place:	D-58579 Schalksmühle	
Telephone:	+49 2351 66887-0	Telefax: +49 2351 66887-29
E-mail:	info@2direct.de	

1.4. Emergency telephone

+49 2351 66887-0

number:

Only available during office hours.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Aerosol 1; H222-H229

Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Signal word:** Danger**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Bike adhesive lubricant with PTFE, MoS2 RP0024

Revision date: 15.01.2024

Page 2 of 14

Special labelling of certain mixtures

EUH208

Contains Sulfonic acids, petroleum, calcium salts, Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate. May produce an allergic reaction.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
106-97-8	butane			50 - < 55 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Press. Gas (Liq.); H220 H280			
74-98-6	propane			25 - < 30 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Press. Gas (Liq.); H220 H280			
61789-86-4	Sulfonic acids, petroleum, calcium salts			1 - < 2.5 %
	263-093-9		01-2119488992-18	
	Skin Sens. 1B; H317			
	Hydrocarbons, C9, aromatics			0.5 - < 1 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
4259-15-8	Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)			0.1 - < 0.5 %
	224-235-5		01-2119493635-27	
	Eye Dam. 1, Aquatic Chronic 2; H318 H411			
	Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate			< 0.1 %
	947-946-9		01-2120772600-59	
	Skin Irrit. 2, Skin Sens. 1B, Aquatic Chronic 4; H315 H317 H413			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
61789-86-4	263-093-9	Sulfonic acids, petroleum, calcium salts	1 - < 2.5 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 16000 mg/kg Skin Sens. 1B; H317: >= 10 - 100		
	918-668-5	Hydrocarbons, C9, aromatics	0.5 - < 1 %
	dermal: LD50 = > 3160 mg/kg; oral: LD50 = ca. 7093 mg/kg		
4259-15-8	224-235-5	Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	0.1 - < 0.5 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = 3100 mg/kg Eye Dam. 1; H318: >= 50 - 100 Eye Irrit. 2; H319: >= 1 - < 50		

SECTION 4: First aid measures**4.1. Description of first aid measures**

Bike adhesive lubricant with PTFE, MoS2 RP0024

Revision date: 15.01.2024

Page 3 of 14

General information

When in doubt or if symptoms are observed, get medical advice.
If medical advice is needed, have product container or label at hand.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurized container: May burst if heated. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For non-emergency personnel

Remove persons to safety. Ventilate affected area.

For emergency responders

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up

Bike adhesive lubricant with PTFE, MoS2 RP0024

Revision date: 15.01.2024

Page 4 of 14

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Do not pierce or burn, even after use.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Lubricants, greases, release products

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Bike adhesive lubricant with PTFE, MoS2 RP0024

Revision date: 15.01.2024

Page 5 of 14

DNEL/DMEL values

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
61789-86-4	Sulfonic acids, petroleum, calcium salts			
Worker DNEL, long-term		inhalation	systemic	11,75 mg/m³
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1,03 mg/cm²
Consumer DNEL, long-term		inhalation	systemic	2,9 mg/m³
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,513 mg/cm²
Consumer DNEL, long-term		oral	systemic	0,833 mg/kg bw/day
	Hydrocarbons, C9, aromatics			
Consumer DNEL, long-term		inhalation	systemic	32 mg/m³
Consumer DNEL, long-term		dermal	systemic	7,5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	7,5 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	12,5 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	151 mg/m³
4259-15-8	Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)			
Worker DNEL, long-term		inhalation	systemic	6,6 mg/m³
Worker DNEL, long-term		dermal	systemic	9,6 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1,67 mg/m³
Consumer DNEL, long-term		dermal	systemic	4,8 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,19 mg/kg bw/day
	Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate			
Worker DNEL, long-term		inhalation	systemic	4,93 mg/m³
Worker DNEL, long-term		dermal	systemic	1,4 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,87 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,5 mg/kg bw/day

Bike adhesive lubricant with PTFE, MoS2 RP0024

Revision date: 15.01.2024

Page 6 of 14

PNEC values

CAS No	Name of agent	
Environmental compartment		Value
61789-86-4	Sulfonic acids, petroleum, calcium salts	
Freshwater		1 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		1 mg/l
Freshwater sediment		226000000 mg/kg
Marine sediment		226000000 mg/kg
Secondary poisoning		16,667 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		271000000 mg/kg
4259-15-8	Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	
Freshwater		0,004 mg/l
Freshwater (intermittent releases)		0,044 mg/l
Marine water		0,0046 mg/l
Freshwater sediment		0,322 mg/kg
Marine sediment		0,032 mg/kg
Secondary poisoning		8,33 mg/kg
Micro-organisms in sewage treatment plants (STP)		3,8 mg/l
Soil		0,062 mg/kg

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear eye/face protection. Suitable eye protection: goggles. EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Recommended material: Butyl caoutchouc (butyl rubber) (0,4 mm) EN ISO 374

Breakthrough time: ≥ 120 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Suitable respiratory protection apparatus:
Combination filtering device A-P2

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	dark grey
Odour:	like: Mineral oil

Bike adhesive lubricant with PTFE, MoS2 RP0024

Revision date: 15.01.2024

Page 7 of 14

Test method

Melting point/freezing point:	not applicable
Boiling point or initial boiling point and boiling range:	< -20 °C
Flammability:	not determined
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	10,9 vol. %
Flash point:	< -20 °C
Auto-ignition temperature:	365 °C
Decomposition temperature:	not determined
pH-Value:	not applicable
Viscosity / kinematic:	not determined
Water solubility: (at 20 °C)	practically insoluble
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	0,6 g/cm³ calculated.
Relative vapour density:	not determined
Particle characteristics:	not applicable

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties

Heating may cause an explosion.

Sustaining combustion:

No data available

Oxidizing properties

The product is not: oxidising.

Other safety characteristics

Evaporation rate:

not determined

Solid content:

not determined

Viscosity / dynamic:

not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

Extremely flammable aerosol. Pressurized container: May burst if heated.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

Bike adhesive lubricant with PTFE, MoS2 RP0024

Revision date: 15.01.2024

Page 8 of 14

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
61789-86-4	Sulfonic acids, petroleum, calcium salts				
	oral	LD50 > 16000 mg/kg	Rat	Study report (1981)	other: Section 772 .112-21 CFR 40
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1981)	OECD Guideline 402
	Hydrocarbons, C9, aromatics				
	oral	LD50 ca. 7093 mg/kg	Rat	Study report (1995)	OECD Guideline 401
	dermal	LD50 > 3160 mg/kg	Rabbit	Study report (1984)	OECD Guideline 402
4259-15-8	Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)				
	oral	LD50 3100 mg/kg	Rat	Study report (1975)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1975)	OECD Guideline 402

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains Sulfonic acids, petroleum, calcium salts, Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Further information

No further relevant information available.

SECTION 12: Ecological information**12.1. Toxicity**

Bike adhesive lubricant with PTFE, MoS2 RP0024

Revision date: 15.01.2024

Page 9 of 14

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
61789-86-4	Sulfonic acids, petroleum, calcium salts					
	Acute fish toxicity	LL50 > 10000 mg/l	96 h	Cyprinodon variegatus	Study report (1986)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Raphidocelis subcapitata	Study report (1994)	EPA OTS 797.1050
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h		Study report (1993)	EPA OTS 797.1300
	Acute bacteria toxicity	EC50 > 10000 mg/l ()	3 h	activated sludge of a predominantly domestic sewage	Study report (1994)	OECD Guideline 209
	Hydrocarbons, C9, aromatics					
	Acute fish toxicity	LL50 9,2 mg/l	96 h	Oncorhynchus mykiss	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 7,9 mg/l	72 h	Raphidocelis subcapitata	Study report (2006)	OECD Guideline 201
	Acute crustacea toxicity	EL50 3,2 mg/l	48 h		REACH Registration Dossier	OECD Guideline 202
4259-15-8	Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)					
	Acute fish toxicity	LL50 4,4 mg/l	96 h	Oncorhynchus mykiss	Study report (2002)	OECD Guideline 203
	Acute algae toxicity	ErC50 410 mg/l	72 h	Desmodesmus subspicatus	Study report (2004)	OECD Guideline 201
	Acute crustacea toxicity	EL50 75 mg/l	48 h		Study report (2005)	OECD Guideline 202
	Crustacea toxicity	NOEC 0,4 mg/l	21 d		Study report (2010)	OECD Guideline 211
	Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate					
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute bacteria toxicity	EC50 > 1000 mg/l ()	3 h	activated sludge of a predominantly domestic sewage	REACH Registration Dossier	OECD Guideline 209

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36
61789-86-4	Sulfonic acids, petroleum, calcium salts	> 4,46
	Hydrocarbons, C9, aromatics	>= 3,03
4259-15-8	Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	3,59

Bike adhesive lubricant with PTFE, MoS2 RP0024

Revision date: 15.01.2024

Page 10 of 14

BCF

CAS No	Chemical name	BCF	Species	Source
	Hydrocarbons, C9, aromatics	>= 30,85		REACH Registration D

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1

Bike adhesive lubricant with PTFE, MoS2 RP0024

Revision date: 15.01.2024

Page 11 of 14



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: 63 190 277 327 344 381 959
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS, FLAMMABLE
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: A145 A167 A802
Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):
Entry 3, Entry 40

Bike adhesive lubricant with PTFE, MoS2 RP0024

Revision date: 15.01.2024

Page 12 of 14

Directive 2010/75/EU on industrial emissions:	80,604 % (483,624 g/l)
Directive 2004/42/EC on VOC in paints and varnishes:	80,604 % (483,624 g/l)
Information according to Directive 2012/18/EU (SEVESO III):	P3a FLAMMABLE AEROSOLS

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC , 2008/47/EC
Aerosol Directive (75/324/).

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	1 - slightly hazardous to water
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 4,7,8,9,12,15.

Bike adhesive lubricant with PTFE, MoS2 RP0024

Revision date: 15.01.2024

Page 13 of 14

Abbreviations and acronyms

Flam. Gas: Flammable gases
Aerosol: Aerosols
Press. Gas (Liq.): Liquefied gas
Flam. Liq: Flammable liquid
Asp. Tox: Aspiration hazard
Skin Irrit: Skin irritation
Eye Dam: Eye damage
Eye Irrit: Eye irritation
Skin Sens: Skin sensitisation
STOT SE: Specific target organ toxicity - single exposure
Aquatic Chronic: Chronic aquatic hazard
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).
EC/EEC: European Community/European Economic Community
EU: European Union
M-factor: Multiplying factor
IATA: International Air Transport Association
DGR: Dangerous Goods Regulations

Bike adhesive lubricant with PTFE, MoS2 RP0024

Revision date: 15.01.2024

Page 14 of 14

ICAO: International Civil Aviation Organization

TI: Technical Instructions

VOC: volatile organic compound

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Eye Irrit. 2; H319	Bridging principle "Aerosols"

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains Sulfonic acids, petroleum, calcium salts, Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)