



# LogiLink®



## Toslink Audio Cable, 1.5 m

Toslink male to Toslink male

Art. No.: CAB1101



Our Toslink Cable is gold plated for optimized connectivity, longevity and signal strength. The fiber-optic tip is precision-polished for maximum signal transfer. Use our premium Toslink Cable to transfer 100% digital optical audio from Dolby Digital receivers, Digital Signal Processors, DivX Players, DVD players, CD players, DSS receivers, Sony Playstation, Xbox and much more.



### Technical Parameters

Fiber Diameter	1 mm
Outside Diameter	2.2 mm
Fiber Material	PMMA
Application Lighwave	650 nm
Attenuation	≤ 0.18 dB/m
Bend Radius	5x core diameter
Used Temperature	-15–80°
Connection Loss	≤0.5 dB
PVC Diameter	5.0+0.2 mm

### Fiber Specification

Center Core	Material Construct mm/No. O.D. mm	Plastic Fiber 0.98 mm x 1 0.98
Outer Coating	Material O.D. mm Color	PE 2.2 Black
Outer Sheath	Material O.D. mm Color	PVC 5.0±0.2 Black

### Package Content:

- » 1 x Toslink to Toslink Cable, 1.5 m

### Package Information:

- » Packing Dimension: 173 x 40 x 260 mm
- » Packing Weight: 0.15 kg
- » Carton Dimension: 420 x 366 x 285 mm
- » Carton Q'ty: 20 pcs
- » Carton Weight: 3 kg



\*The specifications and pictures are subject to change without prior notice.  
\*All trade names referenced are the registered trademarks of their respective owners.



Made in China