# LogiLink®

### Wireless Smart Plug

Art. No.: SH0101

Cogilinto

### Build Your Smart Home

Manage indoor devices, such as lamps, kettle, chargers or television via free smartphone app using Wi-Fi connection.





#### App Remote Control

Smart Plug can be controlled through your existing Wi-Fi network via the free *Smart Life* or *Megos Smart Home* app.





Smart Life

**Megos Smart Home** 

Download the free APP from the App Store or Google Play store.









IP20





#### Set Your Unique Schedule and Timer

Create a schedule or timer to power on/off any of your home electronics or appliances.



#### **Control Your Appliances from Anywhere**

Turn on/off connected appliances wherever you are through your smartphone at any time.



## Works with Amazon Alexa and Google Home

Manage your home devices through voice control to make your life effortless.

#### **Specifications:**

Wireless StandardIEEE 802.11b/g/nWireless Frequency Range2.412-2.472 MHzMax. Transmission Power100 mWRated Voltage230 V AC 50/60 Hz, 16 AMax. Output Power3840 WPlugSafety plug CEE 7/7SocketGerman socket CEE 7/3Operation Distance (In Open Area)100-300 mSafety ShutterYesProtectionsOver-current and over-voltage protectionsProtection ClassIP20Operating Temperature-20-55°COperating Humidity45-75% RH (non-condensing)ColorWhiteProduct Dimension5,6 x 5 x 8,3 cmProduct Weight83,8 gSystem RequirementsAndroid 5 or above / iOS 11 or above		
Max. Transmission Power100 mWRated Voltage230 V AC 50/60 Hz, 16 AMax. Output Power3840 WPlugSafety plug CEE 7/7SocketGerman socket CEE 7/3Operation Distance (In Open Area)100–300 mSafety ShutterYesProtectionsOver-current and over-voltage protectionsProtection ClassIP20Operating Temperature-20–55°COperating Humidity45–75% RH (non-condensing)ColorWhiteProduct Dimension5,6 x 5 x 8,3 cmProduct Weight83,8 g	Wireless Standard	IEEE 802.11b/g/n
Rated Voltage230 V AC 50/60 Hz, 16 AMax. Output Power3840 WPlugSafety plug CEE 7/7SocketGerman socket CEE 7/3Operation Distance (In Open Area)100–300 mSafety ShutterYesProtectionsOver-current and over-voltage protectionsProtection ClassIP20Operating Temperature-20–55°COperating Humidity45–75% RH (non-condensing)ColorWhiteProduct Dimension5,6 x 5 x 8,3 cmProduct Weight83,8 g	Wireless Frequency Range	2.412–2.472 MHz
Max. Output Power3840 WPlugSafety plug CEE 7/7SocketGerman socket CEE 7/3Operation Distance (In Open Area)100–300 mSafety ShutterYesProtectionsOver-current and over-voltage protectionsProtection ClassIP20Operating Temperature-20–55°COperating Humidity45–75% RH (non-condensing)ColorWhiteProduct Dimension5,6 x 5 x 8,3 cmProduct Weight83,8 g	Max. Transmission Power	100 mW
PlugSafety plug CEE 7/7SocketGerman socket CEE 7/3Operation Distance (In Open Area)100–300 mSafety ShutterYesProtectionsOver-current and over-voltage protectionsProtection ClassIP20Operating Temperature-20–55°COperating Humidity45–75% RH (non-condensing)ColorWhiteProduct Dimension5,6 x 5 x 8,3 cmProduct Weight83,8 g	Rated Voltage	230 V AC 50/60 Hz, 16 A
SocketGerman socket CEE 7/3Operation Distance (In Open Area)100–300 mSafety ShutterYesProtectionsOver-current and over-voltage protectionsProtection ClassIP20Operating Temperature-20–55°COperating Humidity45–75% RH (non-condensing)ColorWhiteProduct Dimension5,6 x 5 x 8,3 cmProduct Weight83,8 g	Max. Output Power	3840 W
Operation Distance (In Open Area)100–300 mSafety ShutterYesProtectionsOver-current and over-voltage protectionsProtection ClassIP20Operating Temperature-20–55°COperating Humidity45–75% RH (non-condensing)ColorWhiteProduct Dimension5,6 x 5 x 8,3 cmProduct Weight83,8 g	Plug	Safety plug CEE 7/7
Safety ShutterYesProtectionsOver-current and over-voltage protectionsProtection ClassIP20Operating Temperature-20–55°COperating Humidity45–75% RH (non-condensing)ColorWhiteProduct Dimension5,6 x 5 x 8,3 cmProduct Weight83,8 g	Socket	German socket CEE 7/3
ProtectionsOver-current and over-voltage protectionsProtection ClassIP20Operating Temperature-20–55°COperating Humidity45–75% RH (non-condensing)ColorWhiteProduct Dimension5,6 x 5 x 8,3 cmProduct Weight83,8 g	Operation Distance (In Open Area)	100–300 m
Protection ClassIP20Operating Temperature-20–55°COperating Humidity45–75% RH (non-condensing)ColorWhiteProduct Dimension5,6 x 5 x 8,3 cmProduct Weight83,8 g	Safety Shutter	Yes
Operating Temperature-20-55°COperating Humidity45-75% RH (non-condensing)ColorWhiteProduct Dimension5,6 x 5 x 8,3 cmProduct Weight83,8 g	Protections	Over-current and over-voltage protections
Operating Humidity45–75% RH (non-condensing)ColorWhiteProduct Dimension5,6 x 5 x 8,3 cmProduct Weight83,8 g	Protection Class	IP20
ColorWhiteProduct Dimension5,6 x 5 x 8,3 cmProduct Weight83,8 g	Operating Temperature	-20–55°C
Product Dimension5,6 x 5 x 8,3 cmProduct Weight83,8 g	Operating Humidity	45–75% RH (non-condensing)
Product Weight 83,8 g	Color	White
	Product Dimension	5,6 x 5 x 8,3 cm
System Requirements Android 5 or above / iOS 11 or above	Product Weight	83,8 g
	System Requirements	Android 5 or above / iOS 11 or above

#### Package Contents:

» 1x Wi-Fi Smart Plug

» 1x User Manual

#### Package Information:

- » Packing Dimension: 55 x 55 x 87 mm
- » Packing Weight: 0,095 kg
- » Carton Dimension: 375 x 300 x 320 mm
- » Carton Q'ty: 100 pcs
- » Carton Weight: 10,11 kg







