



LogiLink®

Audio Converter


Analog to Digital SPDIF/COAX

Art. No.: CA0102

Experience premium hearing quality with LogiLink Audio Converter, converting analog L/R audio to digital coaxial and Toslink audio signals simultaneously.


Features:

- » Supports uncompressed 2-channel LPCM digital audio signal output
- » Output sampling rate at 48 kHz
- » Provides electromagnetic-noise-free transmission
- » Easy to install and simple to operate



Speaker


Output



Input



Blu-ray/DVD



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.



CA0102

v3



Made in China

Specification:

Input Ports	2x Cinch (L/R audio)
Output Ports	1x Toslink (SPDIF/Optical), 1x digital coaxial (RCA) female
Sampling Rate	48 kHz
SPDIF Interface	Yes
Uncompressed Audio	LPCM 2.0
Power Supply	DC 5 V/1 A (5 W max.)
Power Consumption	0.5 W max.
Operating Temperature	0–70°C
Operating Humidity	10–85 % RH (no condensation)
Housing Material	Metal
Dimensions	5.1 x 4.1 x 2.6 cm
Weight	0.07 kg

Specification of External Power Supply:

Input Voltage	100–240 V, 50/60 Hz 0.2 A max.
Output Power	5 V/1 A, 5 W
DC Plug	5.5 x 2.1 mm
Dimensions	51 x 35 x 59 mm
Cable Length	1.2 m
Weight	0.07 kg



Package Contents:

- » 1 x Audio Converter
- » 1 x Power Supply
- » 1 x User Manual

Package Information:

- » Packing Dimension: 149 x 110 x 40 mm
- » Packing Weight: 0.26 kg
- » Carton Dimension: 575 x 235 x 340 mm
- » Carton Q'ty: 50 pcs
- » Carton Weight: 11.1 kg



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.

