

LogiLink®



HDMI™ Extender Set via Network Cable

1080p/60 Hz, Extend up to 50 m

Art. No.: HD0057

Allows you to extend HDMI video/audio and USB signals by up to 50 m over a networking cable; with resolution up to 1080p/60 Hz and two USB 2.0 connections. Also, it works to extend IR signals from remote controls of the video source.

Features:

- » Supports 1080P/60 Hz up to 50 m over a single Cat. 5e/6/7/8 cable
- » Bandwidth: 2,25 Gbps/225 MHz per channel
- » Supports 12 bit per channel (36 bit all channels) deep color
- » Compatible with HDCP 1.3 and supports Full 3D, IR, LAN and KVM functions
- » Supports uncompressed audio such as LPCM 7.1
- » Supports compressed audio such as DTS, Dolby Digital (including DTS-HD Master Audio™ and Dolby TrueHD)
- » Compatible with Windows, Mac OS and Linux OS
- » Plug and Play, no software installation required

Transmitter



Receiver



- (a) Connection LED indication.
- (b) Reset button
- (c) Connect to DC 5 V power supply.
- (d) Connect to output device (HDMI TV/monitor) via HDMI male output port.
- (e) Connect to input source via HDMI male input port.
- (f) IR signal output port.
- (g) Connect the network cable to Receiver.
- (h) Connection to PC or Laptop for data transmit or controlling the Receiver's USB-D slots.
- (i) IR signal input port.
- (j) Connect the network cable to Transmitter.
- (k) Connect to USB peripherals such as keyboard and mouse.



HD0057




Made in China



*The specifications and pictures are subject to change without prior notice.

*All trade names referenced are the registered trademarks of their respective owners.



Specifications:

Transmitter (TX) Interface	1x RJ45 Jack, 2x HDMI-A female, 1x USB-B female, 1x DC power jack, 1x IR port
Receiver (RX) Interface	1x RJ45 Jack, 1x HDMI-A female, 2x USB-A female, 1x DC power jack, 1x IR port
HDMI Version	1.3
HDCP Version	1.3 (only support on Transmitter)
Working Distance	50 m
Output Resolution	480i@60 Hz, 576i@50 Hz, 1080i@50/60 Hz, 480p@60 Hz, 576p@50Hz, 720p@50/60 Hz, 1080p@24/25/30/50/60 Hz
Video Bandwidth	2.25 Gbps/225 MHz
Deep Color	12 bit
IR Support	Yes
3D Support	Yes
KVM Support	Yes
DDC (Display Data Channel)	Yes
HDMI Loop Out	Yes
Chassis Material	Yes
Power Consumption	TX: 2 W, RX: 1 W
Power Supply	5 V/1 A (5 W)
Uncompressed Audio	LPCM 7.1
Compressed Audio	DTS, Dolby Digital, DTS-HD Master Audio™, Dolby TrueHD
Networking Cable	Cat.5e/6/7/8



*The specifications and pictures are subject to change without prior notice.
 *All trade names referenced are the registered trademarks of their respective owners.



HD0057



4 052792 067491

Made in China

Operating Temperature	0–70°C
Operating Humidity	10–85% RH (no condensation)
Dimensions	TX: 14.5 x 6.9 x 2.5 cm; RX: 14.5 x 6.9 x 2.5 cm
Weight	TX: 245 g; RX: 245 g

Specification of External Power Supply:

Input Voltage	100–240 V, 50/60 Hz 0.2 A max.
Output Power	5 V/1 A, 5 W
DC Plug	5.5 x 2.1 mm
Dimensions	51 x 35 x 59 mm
Cable Length	1.2 m
Weight	0.07 kg



Package Contents:

- » 1x HDMI Extender Set
- » 2x IR Cables
- » 4x Mounting Ears
- » 2x Power Adapters 5 V/1 A
- » 1x User Manual

Package Information:

- » Packing Dimension: 320 x 237 x 55 mm
- » Packing Weight: 0.97 kg
- » Carton Dimension: 575 x 255 x 360 mm
- » Carton Q'ty: 10 pcs
- » Carton Weight: 10.4 kg



*The specifications and pictures are subject to change without prior notice.
 *All trade names referenced are the registered trademarks of their respective owners.

