

USB-C Multiport Mini Dock with Power Pass-Through UH3236

The UH3236 connects a USB-C enabled computer to up to 5 peripheral ports that includes a USB 2.0 Type-A, USB 3.1 Gen 1 Type-A, Gigabit LAN, HDMI, and VGA – through a single USB-C cable. The UH3236 routes video from a source computer to a 4K HDMI (3840 x 2160 @ 30 Hz) or VGA (1920 x 1200 @ 60 Hz) monitor via a single cable.

This dock provides one USB 3.1 Gen 1 Type-A port for 5 Gbps high-speed data transfers and one USB 2.0 Type-A port for keyboard and mouse usage. The UH3236 also supports USB-C Power Delivery Pass-Through to up to 60W, which means it can provide power to your laptops via a USB-C power adapter with PD profile specifications of 5V, 9V, 12V, 15V, 20V.

With UH3236, users can save desk space, and expand devices connectivity, and creates a personalized desktop environment. This powerful and versatile dock offers a perfect portable solution for connecting multiple sources to a USB-C enabled computer.



- Supports 4K HDMI (3840 x 2160 @ 30Hz) resolutions; or VGA (1920 x 1200 @ 60Hz) resolutions
- Supports USB Power Delivery 3.0 for laptop charging up to 60W via USB-C power adapter – power profiles include 5V, 9V, 12V, 15V, 20V**
- Gigabit Ethernet port
- Plug & Play no drivers needed
- Works with all major operating systems: Windows^{®,} OS X®, and Android***
- * With Intel 7th-Generation Core Processor (Kaby Lake) and above. For video output to work through a USB-C port, it must support DP Alt Mode.
- **The total charging time may vary depending on the spec of USB-C power adapter connected to the UH3236.
- *** Support mirror mode only.

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767 www.aten.com E-mail: marketing@aten.com



Specifications

Function	UH3236
Computer Connections	1
Cable Length	35 cm
Connectors	
Computer	1 x USB-C Male (Black)
Device	1 x USB 2.0 Type A Female (Black) 1 x USB 3.1 Gen1 Type A Female (Blue)
Video Output	1 x HDMI Female (Black) 1 x VGA Female (Black)
LAN Ports	1 x Gigabit Ethernet Female (Black)
Power	1 x USB-C Female Support Power Delivery 3.0 for laptop charging up to 60W* *USB-C Power Adapter from laptop is needed for Power Delivery Pass-Through function.
Video Resolution	Single View: HDMI - 3840 x 2160 @ 30Hz or VGA - 1920 x 1200 @ 60Hz
Power Consumption	DC 5V , 12.5W
Environmental	
Operating Temperature	0° - 40° C
Storage Temperature	-20° - 60° C
Humidity	0 - 80% RH, Non-condensing
Physical Properties	
Housing	Plastic
Weight	0.08 kg
Dimensions (L x W x H)	14.00 x 5.50 x 1.60 cm

Product information is subject to change without prior notice.

Publish Date: 11/2018 V1.0

