

Charging cable Mode3 Typ2 32A 3ph 7,5m



•	
Part number	08 91 409 0102 A0
Specification	Charging cable Mode3 Typ2 32A 3ph 7,5m
HARTING eCatalogue	https://b2b.harting.com/08914090102A0

Image is for illustration purposes only. Please refer to product description.

Identification

Element	Charging cable
Specification	Straight
Charging mode	Mode 3
Connector 1	Type 2 Female (Vehicle side)
Connector 2	Type 2 Male (infrastructure side)
Version	
Cable length	7.5 m
Core structure	5x 6 mm² + 0.5 mm²
Termination method	
	Crimp termination
Number of phases	Crimp termination 3
Number of phases	3
Number of phases Number of contacts	3 7
Number of phases Number of contacts Number of signal contacts	3 7 2
Number of phases Number of contacts Number of signal contacts Number of power contacts	3 7 2 5 Signal: CP, PP

Technical characteristics

Rated current (signal)	2 A
Rated voltage (signal)	30 V
Rated current (power)	32 A

Page 1 / 3 | Creation date 2022-10-05 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Automotive GmbH | Marienwerderstraße 2 | D-32339 Espelkamp | Germany



Technical characteristics

Rated voltage (power)	480 V
Type of current	AC
Charging power	22 kW
Coding resistance	220 Ω between PE and PP
Ambient temperature	-30 +50 °C in operation -40 +80 °C storage/transport
Air pressure	≥540 hPa ≈ 5000 m
Insertion force	<100 N
Withdrawal force	<100 N
Mating cycles	≥10,000
Degree of protection acc. to IEC 60529	IP44 mated condition
Cable diameter	16.5 mm ± 0.3 mm
Minimum bending radius	9x Cable diameter (repeated bending)
Conductor resistance @ 20 °C	≤3.3 Ω/km @ 6 mm² ≤39 Ω/km @ 0.5 mm²

Material properties

Material (insert)	Polyamide (PA)
Colour (insert)	Black
Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (hood/housing)	Polyamide (PA)
Colour (hood/housing)	Black
Material (cover)	Thermoplastic polyurethane (TPU)
Material (cable)	Thermoplastic polyurethane (TPU)
Colour (cable)	Black
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes

Page 2 / 3 | Creation date 2022-10-05 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Automotive GmbH | Marienwerderstraße 2 | D-32339 Espelkamp | Germany



Material properties

REACH SVHC substances	Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

Specifications and approvals

Specifications	IEC 62196-2 IEC 62893
CE	Yes

Commercial data

Packaging size	1
Net weight	4 kg
Country of origin	Romania
European customs tariff number	85444290
GTIN	5713140162570
eCl@ss	27144705 Charging cable E-Mobility