



## 17" FULL HD LCD 1-Port KVM Console

### HDMI KVM Module Features

Single USB console control 1HDMI interface computer and two additional USB device

Supports USB TYPE A interface type keyboard and mouse device

HDMI LCD Console resolution in Optimum:1920x1080p@60 Hz

KVM module resolution in Max: 4K@30 Hz (3840x2610@30 Hz)

Switch the computer through the front panel buttons, keyboard hotkeys and screen menu (OSD)

Connect to the controlled device for BIOS-level access without worrying about the risk of viruses and Trojans

The controlled computer does not need to install any software and drivers, and the controlled computer directly recognizes KVM

Upgrade remote network control mode by extending IP BOX

Supports OSD to set user login mode and increase KVM login security requirements

Supports widescreen resolution

Supports DDC communication to adapt to different graphics devices

Auto scan function monitors all computer operations

Supports for cross-platform operations - Windows, Linux, Mac, and Sun

Art-No.	Keyboard Layout	EAN Code
LC703GE	DE (German)	4052792065824
LC703US	US (English)	4052792065831

## 17" High-Definition Monitor Specifications

LCD Monitor	Ratio	17,3" Screen, 16:9
	Video	Wide AHVA TFT-LCD
	Visible Square	381,888(H)x214,812(V)
	Resolution	1920x1080@60 Hz
	Support Color	16,7M (RGB 6-bit data+ HiFCR data)
	Contrast	600:1 (Typ)
	Back Light	LED
	Pixel Pitch	0,1989 (per one triad)x0,1989
	LED MTBF	100.000 hours
	Input power	12V
Keyboard (demountable design)	Keyboard	100Keys, detachable (9 different languages for choose)
	Compatible IBM/AT	Microsoft Windows 9, Me/NT/2000/XP, Win 7, Server 2003, Win 8, Win 10
	Port	Standard PS/2; USB
	Using Life	>1.000.000 Times
Mouse	Type	Touch Screen
	Port	Standard PS/2
	X/Y Resolution	>1000dots/inch, (40x40/mm)
	Using Life	>1.000.000 Times
Installation Dimension	40,7x44,5x4,5 cm	
Weight	8,5 kg	



## KVM Module Specifications

Computer Connection	1		
Port Selection	OSD menu, Front panel switches, Hot key		
Connector	Console Connector	Monitor	1x HDMI Female
		Keyboard	1x USB Type A Female
	PC Connector	Mouse	1x USB Type A Female
		Monitor	1x HDMI Female
	Mouse/Keyboard	1x USB TYPE B Female	
Power	Power Supply	1x DC Jack	
Key Switch	KVM Switch Reset	1x Semi-embedded keys	
Simulation Method	Keyboard & Mouse	USB	
Max Resolution Video	4K@30 Hz (3840x2610@ 30Hz)		
Scan Interval	3, 5, 10, 15, 20, 30, 40, 60 seconds (Default 3 Seconds)		
Operating Environment	Operating Temperature	0–50°C	
	Storage Temperature	-20–60°C	
	Humidity	0–80% RH (no condensation)	
Physical Properties	Housing	Metal	
	Dimensions (LxWxH)	43,2x15,5x4,4 cm	
	Weight	0,28 kg	

## Package Contents

1x 17" Full HD LCD 1-Port KVM Console

1x User Manual

## Packaging Informations

Packing Dimension	755x625x186 mm
Packing Weight	13,97 kg
Carton Dimension	755x625x186 mm
Carton Q'ty	1 pcs
Carton Weight	13,97 kg