

LogiLink®


HDMI™ Switch, 3x1 Ports
1080p/60 Hz, Remote Control

Art. No.: **HD0042**

Designed for applications that require the routing of 3 sources to 1 compatible display device. It enables the reliable transmission at video resolutions up to 1080p@60 Hz. Features auto and manual switching modes for selection; instantly switching for a smooth video transition between HDMI ports.

Features:

- » Allows up to three HDMI sources to be connected to one HDMI display
- » Supports manual switching, remote switching or automatic switching
- » Resolution up to Full HD 1080p@60 Hz
- » Bandwidth up to 7.5 Gbps (2.5 Gbps at 250 MHz per channel)
- » Supports 3D and HDCP pass-through
- » Supports Consumer Electronics Control (CEC)
- » Supports 36 bit Deep Color (12 bit per channel)
- » Supports LPCM 7.1, Dolby TrueHD and DTS-HD Master Audio™
- » Perfect solution for home, schools, bars and restaurants





Specifications:

Input (Source)	3x HDMI-A female, 1x 3.5 mm jack for IR
Output (Display)	1x HDMI-A female
HDMI Standard	1.3
HDCP	Pass through
Output Resolution	480i/60 Hz, 576i/50 Hz, 1080i/50/60 Hz, 480p/60 Hz, 576p/50 Hz, 720p/50/60 Hz, 1080p/24/25/30/50/60 Hz
CEC (Consumer Electronics Control)	Yes
DDC (Display Data Channel)	Yes
3D Supporting	Yes
Video Bandwith	Up to 7.5 Gbps
TMDS	Yes
Max. TMDS Character Rate	250 MHz
Max. Data Rate	6 Gbps
Data Channels	3
Color Format Support	RGB/YCbCr4:4:4/YCbCr4:2:2
Color Depth Support	12 bit
Switch	Select button
Uncompressed Audio	LPCM 7.1
Compressed Audio	DTS-HD Master Audio™, Dolby TrueHD
Standby Power Consumption	0.5 W
Power Supply	HDMI bus powered
Hot Plug and Plug & Play	Yes
LED Indication	Yes
IR Remote Control	Yes
Remote Control Battery	1x CR2025
Working Distance of Remote	Up to 5 m
Chassis Material	ABS
Color	Black
Operating Temperature	0-70°C
Operating Humidity	10–85% RH (no condensation)
Dimensions	8 x 5.8 x 1.8 cm
Weight	54 g

Package Contents:

- » 1x HDMI Switch
- » 1x Remote Control
- » 1x IR Receiver
- » 1x User Manual

Package Information:

» Packing Dimension: 160 x 107 x 50 mm

» Packing Weight: 0.16 kg

» Carton Dimension: 575 x 255 x 345 mm

» Carton Q'ty: 40 pcs

