LogiLink

Portable Power Station 300 W Art. No.: PPS0300



High Performance Outdoor Power Solution

LogiLink's Portable Power Station is engineered to provide reusable, rechargeable portable power for a variety of applications. It is safe to use with built-in intelligent cooling system, multiple charging protections and eco-friendly. Perfect for road trip, camping or during a power outage.





Car











LiFeP04 Battery

Solar Power

-Ò.

Charge

Fast Charge

Flashlight

Safe to Use

Eco-Friendly

Easy to Transport

Long Lasting & Safe Power Solution

The durable, stable and efficient Lithium iron phosphate (LiFePO4) battery works with solar charging, supplying off-grid power to your needs.





6 Output Ports Can Be Used Simultaneously

Equipped with 6 charging output ports and it have 3 output modes of AC, USB and car charger. Compatible with multiple electrical devices at the same time.



2x USB-A + 2x USB-C Outputs Up to 65 W Fast Charging

Emergency LED Light

4 brightness levels and SOS lighting to lit up the camping ground.

Large & Clear LCD Display

Easy to read LCD display allows user to see the power supply quantity and charging efficiency at a glance.



3 Charging Modes

Quick recharge through solar panel, AC or car.

Wall





Solar Charging

Charging

Charging



Multiple Safety Protections

Reliable with 8 kinds of security protections and make daily use more secure.

Undervoltage





Overtemperature

Cryogenic

].



Short Circuit

Overcurrent



Overload

SOH Monitor

Compatible with LogiLink Foldable Solar Panels, Solar Cables and Cigarette Lighter to Alligator Clip Cable.



PHC0400/PHC0401

CP0400

PVP0100/PVP0200

Specifications:

Battery Type	LiFePO4
Battery Capacity	204.8 Wh, 25.6 V DC 8 Ah
Battery Life Cycle	3000 cycles
Inputs	AC: 220–240 V~, 50/60 Hz, 3 A (550 W max.) Solar panel: 12–24 V/8 A (120 W max.) Car charging: 12 V/8 A (96 W max.)
Outputs	AC: 220–240 V~, 50/60 Hz, 1.5 A max. Car charger: 12.6 V/8 A (100 W max.) USB-A1/A2: 5 V/2.4 A (12 W max.) USB-C1/C2: 5 V/3 A (15 W), 9 V/3 A (27 W), 12 V/3 A (36 W), 15 V/3 A (45 W) 20 V/3.25 A (65 W max.) USB-C1+C2: 5 V/3 A (15 W), 9 V/3 A (27 W), 12 V/2.5 A (30 W), 15 V/2 A (30 W), 20 V/1.5 A (30 W) Total 60 W max. Total outputs: 300 W max.
Protections	Over temperature, low temperature, over-discharge, overcharge, overcurrent, overload and short circuit
IP Rating	IP20
Discharge Temperature	-20-45°C
Charge Temperature	0–45°C
Dimensions	24.8 x 15.8 x 15.2 cm
Weight	4 kg
AC Cable Length	1.5 m

Package Contents:

- » 1x Power Station
- » 1x AC Cable
- » 1x Car Charging Cable
- » 1x User Manual

Package Information:

- » Packing Dimension: 274 x 189 x 228 mm
- » Packing Weight: kg
- » Carton Dimension: 395 x 291 x 481 mm
- » Carton Q'ty: 4 pcs
- » Carton Weight: kg



