

Model: **CS-62A**  
2 Port PS/2 KVM Switch



Connection Panel

Model: **CS-64A**  
4 Port PS/2 KVM Switch



Connection Panel

The CS-62A/CS-64A feature a 50% smaller desktop footprint than traditional compact KVM switches. With built-in custom KVM cables and a single molded plastic/metal exterior, this rugged KVM switch offers the most utility for its size.

### Features

- Controls 2 to 4 computers from a single PS/2 console with speaker
- LED display for easy monitoring
- Built in 4' cables (CS-62A), 6' cables (CS-64A) make installation a cinch
- All-in-one design
- Auto Scanning
- With speaker support
- ATEN ASIC inside (CS-64A)

### Specifications

Function	CS-62A	CS-64A	
Computer Connections	2	4	
Computer Port Selection	Hotkey		
Connectors	Console	Keyboard	1 x Mini Din 6 Female (Purple)
		Video	1 x HDB15 Female (Blue)
		Mouse	1 x Mini Din 6 Female (Green)
		Speaker	1 x Mini Stereo Jack Female (Green)
	Computer	Keyboard	2 x Mini Din 6 Male (Purple)
		Video	2 x HDB15 Male (Blue)
		Mouse	2 x Mini Din 6 Male (Green)
		Speaker	2 x Mini Stereo Plug Male (Green)
LEDs	Selected	2 (Green)	
Emulation	Keyboard	PS/2	
	Mouse	PS/2	
Video	2048 x 1536, DDC2B		
Scan Interval	3, 5, 10, 20 Seconds	5 Seconds	
Environment	Operating Temperature	0°~50°C	
	Storage Temperature	-20°~60°C	
	Humidity	0~80% RH, NC	
Physical Properties	Housing	Plastic	
	Weight	0.41 kg	0.9 kg
	Dimensions (L x W x H)	12 x 4.95 x 2.5 cm	8.95 x 7.19 x 2.6 cm

### Diagram

