

Charging cable Mode3 Typ2 20A 3ph 10m



•	
Part number	08 91 409 0111 A0
Specification	Charging cable Mode3 Typ2 20A 3ph 10m
HARTING eCatalogue	https://b2b.harting.com/08914090111A0

Image is for illustration purposes only. Please refer to product description.

Identification

Element	Charging cable
Specification	Straight
Charging mode	Mode 3
Connector 1	Type 2 Female (Vehicle side)
Connector 2	Type 2 Male (infrastructure side)
Version	
Cable length	10 m
Core structure	5x 2.5 mm ² + 0.5 mm ²
Termination method	Crimp termination
Number of phases	3
Number of contacts	7
Number of signal contacts	2
Number of power contacts	5
Contact configuration	Signal: CP, PP Power: L1, L2, L3, N, PE
Details	Also available with customer specific logo on request.

Technical characteristics

Rated current (signal)	2 A
Rated voltage (signal)	30 V
Rated current (power)	20 A

Page 1 / 3 | Creation date 2022-11-12 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Automotive GmbH | Marienwerderstraße 2 | D-32339 Espelkamp | Germany



Technical characteristics

Rated voltage (power)	480 V
Type of current	AC
Charging power	11 kW
Coding resistance	680 Ω between PE and PP
Ambient temperature	-30 +50 °C in operation -40 +80 °C storage/transport
Air pressure	≥540 hPa ≈ 5000 m
Insertion force	<100 N
Withdrawal force	<100 N
Mating cycles	≥10,000
Degree of protection acc. to IEC 60529	IP44 mated condition
Cable diameter	12.8 mm ± 0.4 mm
Minimum bending radius	9x Cable diameter (repeated bending)
Conductor resistance @ 20 °C	≤7.98 Ω/km @ 2.5 mm² ≤39 Ω/km @ 0.5 mm²

Material properties

Material (insert)	Polyamide (PA)
Colour (insert)	Black
Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (hood/housing)	Polyamide (PA)
Colour (hood/housing)	Black
Material (cover)	Thermoplastic polyurethane (TPU)
Material (cable)	Thermoplastic polyurethane (TPU)
Colour (cable)	Black
Material flammability class acc. to UL 94	V-0

Specifications and approvals

Specifications	IEC 62196-2 IEC 62893
CE	Yes
Commercial data	
Packaging size	1

Page 2 / 3 | Creation date 2022-11-12 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Automotive GmbH | Marienwerderstraße 2 | D-32339 Espelkamp | Germany



Commercial data

Net weight	3.085 kg
Country of origin	Romania
European customs tariff number	85444290
GTIN	5713140277502
eCl@ss	27144705 Charging cable E-Mobility

Page 3 / 3 | Creation date 2022-11-12 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Automotive GmbH | Marienwerderstraße 2 | D-32339 Espelkamp | Germany