

## IC485SI

RS-232/RS-485 Interface Converter



IC485SI transfers data according to RTS (transfer requests) signal control. It supports point-to-point and multipoint communication, simplex/duplex connections, and is switchable between full duplex and half duplex, and DCE and DTE. It needs no external power supply and is the most economical and reliable option.



### Features

- Data transmission controlled by the RTS signal.
- DCE/DTE selectable.
- Point to point, multidrop, and simplex/duplex link selection.
- Four wire full duplex; two wire half duplex.
- Compact size.
- Cable distance of up to 1200m (4000 ft.).
- Signal and power isolation.
- Supports baud rates up to 115.2kbps.
- OS Support: Windows 2000, Windows XP

## Specifications

### RS-232/RS-485 Interface Converter

Connectors	1 DB-25 Female (RS-232) RS-485 / RS-422 Four Terminal Block Grounding Tab
Switches	DCE, DTE TxON, RxON TxRTS, RxRTS TxRTS, RxON
Power Consumption	DC9V:0.81W:4BTU
Signal Range	1200 m [4000'] (Max)
Data Rate	Up to 100 Kbps under 1200 m [4000']
Environmental	
Operating Temperature	0 ~50°C
Storage Temperature	-20 ~ 60°C
Humidity	0~80% RH, Non-condensing
Physical Properties	
Housing	Plastic
Weight	0.06 kg ( 0.13 lb )
Dimensions (L x W x H)	7.90 x 5.45 x 2.10 cm (3.11 x 2.15 x 0.83 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram



**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their respective owners.