

LogiLink_®

Maintenance spray

For locks & cylinders

Art. No.: RP0023

The odorless and colorless RP0023 is versatile in the entire care, preservation and maintenance area. It is used for greasing, cleaning and protecting bare metal surfaces with minimal consumption. Its excellent wetting and protective properties result in permanently water-repellent, highly effective anticorrosive and antifriction films. The locking cylinder spray shows neutral behavior towards most plastics, painted surfaces and elastomers. The product is free of grease and sllicone and protects the treated surfaces against icing.

Features:

- » Clean in application and result
- » Temperature resistant from -25 °C to 120 °C
- » Oxidation stable and water resistant

Specifications:

Content	0.15
Fields of application	Precision machine tools, measuring tools, precision mechanics and optics, weapons and other machine elements, such as locking mechanisms, threads, hinges, lock cylinders, etc.
Active Substances	Mineral oil raffinate in isoparaffinic solvent

Application:

Bring can to room temperature before use and shake well. Due to the design of the spray head, targeted application is possible even in hard-to-reach places. Practical application is sensibly carried out as continuous maintenance. Flash-off time depending on ambient conditions approx. 5 minutes.

Package Contents:

» 1x Maintenance spray

Packaging Informations:

- » Packing Dimension: mm
- » Packing Weight: kg
- » Carton Dimension: mm
- » Carton Q'ty: pcs
- » Carton Weight: kg







* The specifications and pictures are subject to change without notice.
*All trade names referenced are the registered namework of their respective owners.